



TECHNICAL SPECIFICATION



Gerbür Aqua-Click Natural Collection brings the natural look of real wood flooring with none of the disadvantages. The many benefits are as follows;

Thickness (mm)		4.00
		0.3
Wear Layer (mm)		
Utilization Class		
Coating		PU with DiamondShield™
Embossing		Real Wood Texture
Bevelled		V-grooved
Fiberglass		yes
Installation Method		Floating floor installation
Plank Size		177.8mm x 1219.2mm
Sqm Per Pack		2.1677
Pallet Packing		151.741 / 70 packs
Impact Sound Insulation	ISO 717-2	5 dB
Chemical Resistance	EN423	High Resistance
Residual Indentation	EN433	≤ 0.08mm
Dimensional Stability	EN434	≤ 0.08%
Colour Fastness to Light	EN20105-B02	≥ 6
Slip Resistance	DIN51130	R10
Watertightness	EN13553	No Penetration
Wear Resistance	EN660-2	Group T
Antimicrobial Activity	ASTMG 21-96	Class 0
Fire Rating	EN ISO 9239-1	Bfl - S1
Warranty for Domestic use		Lifetime
Warranty for Commercial use		10 Years

 $Produced\ with\ 100\%\ pure\ vinyl.\ Does\ not\ contain\ recycled\ material\ and\ therefore\ all\ contents\ conform\ to\ EU\ standards.$



EMBOSSING: Registered Emboss Real Wood Structure. Thickness; 4mm. Wear Layer: 0.3mm. Coating; PU with DiamondShield™. Utilization Class; 33/42 Heavy Commercial. Produced with 100% virgin PVC. Satisfies Green Building Standards and earns LEED certification points in Commercial Applications. Gerbür Aqua Click Natural Collection can be completely recycled.Installation; Installed as a Floating Floor. No Underlay or Glue Required.



INHERENT SAFETY FEATURES: Conforms to all regulatory requirements of commercial flammability codes, slip resistant requirements, certified for low VOC emissions for safer indoor air quality and host of other safety codes.

ECO- FRIENDLY: Gerbür luxury vinyl tile products are made with natural, environmentally friendly sustainable materials which are 100% recyclable.