

## TECHNICAL SPECIFICATION

The *Beethoven* series from Gerbur is our entry level laminate flooring. Ideal for those on a budget or with restrictions on the overall height requirement of their flooring and at 8mm overall thickness, it comes with a full 20 years residential warranty as well as the patented Uniclick locking system that is a signature of all Gerbur laminate floors. With ten glorious species/shades of woods to choose from, we believe *Beethoven* laminate from Gerbur offers outstanding value for money when compared to other floor coverings found in the marketplace



PROPERTY	INFO
Dimensions	1215mm x 197mm x 8mm
Finish:	Middle Embossed
Package	10 pieces per carton = 2 .39 m <sup>2</sup>
Production	Direct faced laminate flooring / melamine impregnated paper / core high-density fibreboard made using 50% FSC timber certified by BM TRADA under license, TT-COC-1943
Laying	Must be layed as floating floor
Classification (BS EN 13329)	32: Heavy domestic use AC4: Medium commercial use
Warranty	20 Years Residential Warranty 10 Years Commercial Warranty

### PRODUCT CHARACTERISTICS HDF-BASE


FACTOR	STANDARDS	UNIT	NOMINAL VALUE
Formaldehyde content	EN622- 1	mg/100g	<8 (class E1)
24h swelling	EN 622- 5	%	<17%
Bending strength	EN 622- 5	N/mm <sup>2</sup>	23
Internal bond	EN 622- 5	N/mm <sup>2</sup>	1
Moisture content	EN 622- 1	%	4 to 11

### PRODUCT CHARACTERISTICS OF LAMINATED FLOOR CORE-BOARDS CLASS: 23-3


FACTOR	STANDARDS	UNIT	NOMINAL VALUE
Abrasion	EN 13329	REVS	AC 4: IP 4,000
Impact resistance	EN 13329	N & mm	≥ IC 2
Stain resistance	EN 438.2.15	Scale*	Group 1&2: 5 Group 3:4
Edge swelling	EN 13329	%	≤ 18



ROTATE AND CLICK



HORIZONTAL INSERTION



MEDIUM COMMERCIAL

