

TECHNICAL SPECIFICATION



Gerbur Aqua-Click Stone collection brings the natural look of real stone flooring with none of the disadvantages. The many benefits are as follows:

Thickness (mm)	4.00
Wear Layer (mm)	0.3
Utilization Class	
Coating	PU with DiamondShield™
Embossing	Real Stone Texture
Fiberglass	yes
Installation Method	Floating floor installation
Plank Size	304.8mm x 609.6mm
Sqm Per Pack	1.8578
Pallet Packing	120.757 / 65 packs
Impact Sound Insulation	ISO 717-2
Chemical Resistance	EN423
Residual Indentation	EN433
Dimensional Stability	EN434
Colour Fastness to Light	EN20105-B02
Slip Resistance	DIN51130
Water Resistance	EN13553
Abrasion Resistance	EN660-2
Antimicrobial Activity	ASTMG 21-96
Fire Rating	EN ISO 9239-1
Warranty for Domestic use	Lifetime
Warranty for Commercial use	10 Years

Produced with 100% pure vinyl. Does not contain recycled material and therefore all contents conform to EU standards.



EMBOSSING : Registered Emboss Real Wood Structure. Thickness: 4mm. Wear Layer: 0.3mm. Coating: PU with DiamondShield™. Utilization Class: 33/42 Heavy Commercial. Produced with 100% virgin PVC. Satisfies Green Building Standards and earns LEED certification points in Commercial Applications .Gerbur Aqua Click Stone Collection can be completely recycled Installation: Installed as a Floating Floor. No Underlay or Glue Required.



INHERENT SAFETY FEATURES: Conforms to all regulatory requirements of commercial flammability codes, slip resistant requirements, certified for low VOC emissions for safer indoor air quality and host of other safety codes.

ECO- FRIENDLY : Gerbur luxury vinyl tile products are made with natural, environmentally friendly sustainable materials which are 100% recyclable.